CORS & OPUS WORKSHOP

(Continuously Operating Reference Stations)

Presented by:
Richard Snay & Rick Foote
NOAA's National Geodetic Survey

ACSM ST. Louis, MO March 11, 2007





CORS Information


Web site: http://www.ngs.noaa.gov/CORS

Email: ngs.cors@noaa.gov

Telephone: 301-713-3563



Global Positioning System GPS



GPS Satellite





The Macrometer V1000 -- the first GPS receiver owned by NOAA!!

The GPS Pathfinder – puts a whole new spin on WHEN and WHERE!!

GPS Pathfinder


The world's first*
wristwatch with
built-in GPS
navigation
capabilities.

*According to CASIO data as of April 1999

The new GPS PATHFINDER is the world's first wristwatch designed to receive and process data from the Global Positioning System (GPS) satellites that ring the globe. Made


I osmoning ilmerica for the I mare

Standalone Positioning: Since May 1, 2000




- C/A Code on L1
- No Selective Availability

PSEUDORANGE FROM CODE DATA



Standalone Positioning: By 2011




- C/A Code on L1
- L2C Code on L2
- New Code on L5

GPS ERROR SOURCES

- * Receiver clock error
- * Satellite clock error
- * Satellite orbit error
- * Ionospheric delay
- * Neutral atmosphere delay
- * Multipath
- * Receiver noise










Figure 1 Multipath Description

August 1987 -Ionospheric refraction and Multipath Effects in GPS Carrier Phase Observations Yola Georgiadou and Alfred Kleusberg IUGG XIX General Assembly Meeting, Vancouver, Canada

DIFFERENTIAL GPS POSITIONING




Real-Time Kinematic: Today




- L1 Code and Carrier
- L2 Carrier
- Data Link

CARRIER MODULATION




Real-Time Kinematic: Tomorrow




- L1 Code and Carrier
- L2 Code and Carrier
- L5 Code and Carrier
- Data Link

HOW TO ACHIEVE CM-LEVEL ACCURACY FOR BASELINES LONGER THAN 25 KM

- * OBSERVE FOR SEVERAL HOURS
- * USE DUAL-FREQUECY RECEIVERS
- * POSTPROCESS GPS DATA WITH SOPHISTICATED SOFTWARE
 - USE "PRECISE" IGS ORBITS
 - SOLVE FOR INTEGER AMBIGUITIES
 - SOLVE FOR TROPO DELAYS




Vertical Precision Using Dual-Frequency GPS Carrier Phase Observations 95% Confidence Level




Continuously Operating Reference Stations


CORS Coverage at 100, 200, 300, and 400 KM - January 2007



Regional CORS Coverage



Local CORS Coverage – Seiler MS COOP



CORS SITES





CORS SITES






CORS OVERVIEW


Network contained 1154 sites as of Jan. 2007

- Growing at rate of 15 sites per month
- More than 185 organizations participate in the CORS program
- Provides code range (C/A, P1, P2)
 - and carrier phase observations (L1, L2)



CORS APPLICATIONS

- Postmission Static Positioning (few cm-level accuracy with 15minutes of data, few dm-level accuracy with one minute of data)
- Postmission Kinematic Positioning (dm-level accuracy for an aircraft, a boat, or a land vehicle)
- Geophysics / Crustal Motion
- Meteorology / Water Vapor in Atmosphere
- Space Weather / Free Electrons in Ionosphere



NATIONAL CORS NETWORK

- National CORS network contains 988 sites whose data are available directly from NOAA's National Geodetic Survey in Silver Spring, MD
- GPS data stored in RINEX format
- Data made available to public via:
 - World Wide Web
 - File transfer protocol
- Currently 13 years of CORS data are online for immediate access
- Parallel CORS Data Facility being operated by NOAA's National Geophysical Data Center in Boulder, CO


COOPERATIVE CORS

 GPS base stations whose data are freely disseminated by cooperating organizations

 NGS provides link from its web site to that of each cooperating organization

• Site coordinates must be consistent with the National Spatial Reference System

Positioning America for the Future




National CORS & Cooperative CORS

National CORS	Cooperative CORS
Data are available online via the NGS CORS Web page	Data are available online via the participant's Web page
Data are permanently archived	Data are kept online for at least 30 days
NGS validates positional coordinates every day	NGS validates positional coordinates every day
Site must meet NGS standards	Site must meet the same NGS standards for National CORS




CORS Networks







NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
National Ocean Service
National Geodetic Survey



COMBO CORS


- The term "Combo CORS" designates a station whose GPS data is distributed both by NOAA and by a cooperating organization.
- Such accessibility to CORS data is highly desirable.
- Scripps Institution of Oceanography (LaJolla, CA) distributes data for 900+ sites in the CORS network.





CORS PARTNERS: FEDERAL







Federal Highway Administration
Federal Railway Administration
Federal Aviation Administration
Forecast Systems Laboratory

National Geophysical Data Center


NASA

US Geological Survey


US Army Corps of Engineers

US Air Force

US Naval Observatory



GPS Nominal Constellation
24 Satellites in 6 Orbital Planes
4 Satellites in each Plane
20,200 km Altitude, 55 Degree Inclination



CORS PARTNERS: INTERNATIONAL





NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
National Ocean Service

National Geodetic Survey



CORS Partners: Private Industry

"If you want to see where GPS is going, then keep your eye on the GPS manufacturers."

> Bill Strange Former Manager National CORS Program

Many GPS companies have developed software that provides their customers with automatic access to CORS data for postprocessing activities.





Civil GPS Use

Power Grid Interfaces

Personal Navigation

Trucking & Shipping

Aviation

Recreation

Off shore Drilling

Satellite Ops --Ephemeris, Timing

Surveying & Mapping

Communications -Network
Synchronization
and Timing

Fishing & Boating

P-0025

Railroads

Consumer/Recreational









- \$3.8B market by 2003
- Portable receivers for fishermen, hunters, campers, hobbyists, etc.
- Recreational facilities
- Estimated 40M potential users in the U.S. alone
- Highly elastic demand
- Integration of GPS into cellular phones expected to generate huge volume


Future GPS User Sectors - \$M (Freedonia Group Report - 1997)




Precision Agriculture




Timing Applications





- Some estimate the timing market at \$40-100M
- Communications network synchronization and management
 - Phone, wireless systems
 - LANs, WANs, Internet
- Power grid management and fault location
- Financial transactions
- E-commerce signatures

CORS Applications



Geographic Information Systems (GIS)



Wards and Precincts
Demographics
Structures
Water Utilities
Sewerage
Electrical Utilities
Roads
Boundaries
Land Use
Hydrology
Soils
Topography











LIDAR images of Manhattan before and after 11 SEP 2001



These images are computerized visualizations of elevation information of the World Trade Center from before (July 2000) and after (September 15, 2001) the attack. These maps were produced using an airborne LIDAR (Light Detection and Ranging) system. The LIDAR system creates detailed and highly accurate elevation information by the precise timing of thousands of laser pulses striking the ground surface. These data can be manipulated in the digital environment to create an array of maps and views of the project site and to obtain precise measuresments of structures, debris fields, and other vital information. These images were generated by EarthData (www.earthdata.com), and the aircraft was positioned using CORS data from the NJI2 site which is operated by the New Jersey Institute of Technology.


Hourly Forecast of Precipitable Water



Precipitable water (mm)

Analysis valid 05-Aug-02 16:00Z

MAPPING TOTAL ELECTRON CONTENT (TEC)






NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
National Ocean Service
National Geodetic Survey





Horizontal Velocities Relative to 'Stable' Sites



Vertical Velocities from CORS

